

WEST

## Freeform Search

Database:

US Patents Full-Text Database  
 US Pre-Grant Publication Full-Text Database  
 JPO Abstracts Database  
 EPO Abstracts Database  
 Derwent World Patents Index  
 IBM Technical Disclosure Bulletins

Term:

Display:  Documents in Display Format:  Starting with Number Generate: ☐ Hit List ☒ Hit Count ☐ Side by Side ☐ Image

Search

Clear

Help

Logout

Interrupt

Main Menu

Show S Numbers

Edit S Numbers

Preferences

Cases

## Search History

DATE: Monday, May 26, 2003 [Printable Copy](#) [Create Case](#)Set Name Query

side by side

Hit Count Set Name

result set

DB=USPT; PLUR=YES; OP=ADJ

<u>L9</u>	L8 and ((mode or standby or (data adj2 hold)) near8 (internal near3 clock))	25	<u>L9</u>
<u>L8</u>	L7 and l3 and l2	37	<u>L8</u>
<u>L7</u>	L6 and l5 and l4	213	<u>L7</u>
<u>L6</u>	data near8 (internal near3 clock)	2719	<u>L6</u>
<u>L5</u>	address near8 (internal near3 clock)	914	<u>L5</u>
<u>L4</u>	(command or request) near8 (internal near3 clock)	681	<u>L4</u>
<u>L3</u>	(clock near3 input\$3) near8 (external near2 clock) near8 (internal near3 clock)	437	<u>L3</u>
<u>L2</u>	SDRAM or (synchronous adj4 (memory or storage))	5889	<u>L2</u>
<u>L1</u>	5768213.pn.	1	<u>L1</u>

END OF SEARCH HISTORY

WEST

Help

Logout

Interrupt

Main Menu

Search Form

Posting Counts

Show S Numbers

Edit S Numbers

Preferences

Cases

## Search Results -

Terms	Documents
l8 and l1	48

Database:

US Patents Full-Text Database  
 US Pre-Grant Publication Full-Text Database  
 JPO Abstracts Database  
 EPO Abstracts Database  
 Derwent World Patents Index  
 IBM Technical Disclosure Bulletins

Search:

L9

Refine Search

Recall Text

Clear

## Search History

DATE: Monday, May 26, 2003 [Printable Copy](#) [Create Case](#)Set Name Query

side by side

Hit Count Set Name

result set

DB=USPT; PLUR=YES; OP=ADJ

<u>L9</u>	18 and l1	48	<u>L9</u>
<u>L8</u>	L7 and l2	52	<u>L8</u>
<u>L7</u>	L6 and l5 and l4	207	<u>L7</u>
<u>L6</u>	(internal near3 clock) near8 data	2719	<u>L6</u>
<u>L5</u>	(internal near3 clock) near8 address	914	<u>L5</u>
<u>L4</u>	(internal near3 clock) near8 command	545	<u>L4</u>
<u>L3</u>	(internal near3 clock) near8 command	545	<u>L3</u>
<u>L2</u>	(internal near3 clock) near8 (hold or held or standby or (power adj down))	456	<u>L2</u>
<u>L1</u>	((365/\$)!.CCLS.)	32631	<u>L1</u>

END OF SEARCH HISTORY

**Set Name Query**

side by side

**Hit Count Set Name**

result set

*DB=USPT; PLUR=YES; OP=ADJ*

<u>L18</u>	L17 and (365/\$.ccls.)	59	<u>L18</u>
<u>L17</u>	L16 and (embedded or (one adj chip))	176	<u>L17</u>
<u>L16</u>	L15 and (memory adj2 control\$4)	620	<u>L16</u>
<u>L15</u>	L1 and LSI	3694	<u>L15</u>

*DB=PGPB,JPAB,EPAB,DWPI,TDBD; PLUR=YES; OP=ADJ*

<u>L14</u>	L13 and ((clock adj2 (input or buffer)) near8 activ\$6)	1	<u>L14</u>
<u>L13</u>	L9 and ((input adj2 signal) near6 (compar\$3 or match\$4 or differ\$4 or correspond\$4) near8 (internal adj2 signal))	15	<u>L13</u>
<u>L12</u>	L9 and ((clock near3 (processor or system or external or internal)) near8 (command adj2 buffer) near8 ((hold or (power adj2 down)) adj2 (mode or state)))	2	<u>L12</u>
<u>L11</u>	L9 and ((clock near3 (buffer or input)) near8 (command adj2 input) near8 ((hold or (power adj2 down)) adj2 (mode or state)))	5	<u>L11</u>
<u>L10</u>	L9 and ((clock near3 (buffer or input)) near8 (clock adj2 line) near8 (normal adj2 (mode or state)))	1	<u>L10</u>
<u>L9</u>	(synchronous adj3 memory) or (semiconductor adj integrated adj circuit)	53537	<u>L9</u>

*DB=USPT; PLUR=YES; OP=ADJ*

<u>L8</u>	16 and ((clock adj2 (input or buffer)) near8 activ\$6)	1	<u>L8</u>
<u>L7</u>	16 and ((clock adj2 buffer) near8 activ\$6)	0	<u>L7</u>
<u>L6</u>	L1 and ((input adj2 signal) near6 (compar\$3 or match\$4 or differ\$4 or correspond\$4) near8 (internal adj2 signal))	24	<u>L6</u>
<u>L5</u>	L1 and ((clock near3 (processor or system or external or internal)) near8 (command adj2 buffer) near8 ((hold or (power adj2 down)) adj2 (mode or state)))	0	<u>L5</u>
<u>L4</u>	L1 and ((clock near3 (processor or system or external or internal)) near8 (command adj2 input) near8 ((hold or (power adj2 down)) adj2 (mode or state)))	0	<u>L4</u>
<u>L3</u>	L1 and ((clock near3 (buffer or input)) near8 (command adj2 input) near8 ((hold or (power adj2 down)) adj2 (mode or state)))	1	<u>L3</u>
<u>L2</u>	L1 and ((clock near3 (buffer or input)) near8 (clock adj2 line) near8 (normal adj2 (mode or state)))	0	<u>L2</u>
<u>L1</u>	(synchronous adj3 memory) or (semiconductor adj integrated adj circuit)	22146	<u>L1</u>

END OF SEARCH HISTORY



[> home](#) [> about](#) [> feedback](#) [> login](#)  
US Patent & Trademark Office

## Search Results

### Nothing Found

Your search for [((synchronous <near/4> memory) or (semiconductor integrated)) and ((clock <near/2> (input or buffer)) <sentence> (command <near/2> (input or buffer))) <sentence> ((hold or (power down) ) <near/2> (mode or state)) ] did not return any results.

You can try to rerun it within the Portal.

You may revise it and try your search again below or click advanced search for more options.

```
((synchronous <near/4> memory) or  
(semiconductor integrated)) and  
((clock <near/2> (input or buffer))  
<sentence> (command <near/2> (input  
or buffer))) <sentence> ((hold or  
(power down) ) <near/2> (mode or  
state))  
☐  
☐
```

**SEARCH**[\[Advanced Search\]](#) [\[Search](#)[Help/Tips\]](#)[Complete Search Help and Tips](#)

### The following characters have specialized meaning:

Special Characters	Description
, ( ) [	These characters end a text token.
= > < !	These characters end a text token because they signify the start of a field operator. (! is special: != ends a token.)
` @ \Q < { [ !	These characters signify the start of a delimited token. These are terminated by the end character associated with the start character.

[IEEE HOME](#) | [SEARCH IEEE](#) | [SHOP](#) | [WEB ACCOUNT](#) | [CONTACT IEEE](#)[Membership](#) | [Publications/Services](#) | [Standards](#) | [Conferences](#) | [Careers/Jobs](#)**IEEE Xplore®**  
RELEASE 1.4Welcome  
United States Patent and Trademark Office[Help](#) | [FAQ](#) | [Terms](#) | [IEEE](#) | [Quick Links](#)[» Search Results](#)[Peer Review](#)

Welcome to IEEE Xplore®

Your search matched **[0]** of **[940663]** documents.

- ☐ Home
- ☐ What Can I Access?
- ☐ Log-out

Tables of Contents

- ☐ Journals & Magazines
- ☐ Conference Proceedings
- ☐ Standards

Search

- ☐ By Author
- ☐ Basic
- ☐ Advanced

Member Services

- ☐ Join IEEE
- ☐ Establish IEEE Web Account
- ☐ Access the IEEE Member Digital Library

Print Format

You may refine your search by editing the current search expression or entering a new one the text box. Then click search Again.

((synchronous <near/4> memory) or (semiconductor integrated)) and ((clock <near/2> (

**OR**

Use your browser's back button to return to your original search page.

**Results:****No documents matched your query.**

[Home](#) | [Log-out](#) | [Journals](#) | [Conference Proceedings](#) | [Standards](#) | [Search by Author](#) | [Basic Search](#) | [Advanced Search](#)  
[Join IEEE](#) | [Web Account](#) | [New this week](#) | [OPAC Linking Information](#) | [Your Feedback](#) | [Technical Support](#) | [Email Alerting](#)  
[No Robots Please](#) | [Release Notes](#) | [IEEE Online Publications](#) | [Help](#) | [FAQ](#) | [Terms](#) | [Back to Top](#)

Copyright © 2003 IEEE — All rights reserved